

CEMENT 20



Pneumatic or hydraulic delivery hose for abrasive media such as cement, sand, etc.
WP 20 BAR

TECHNICAL CHARACTERISTICS

TUBE	Black special antistatic rubber tube; High abrasion resistant.
REINFORCEMENT	High tensile textile reinforcement;
COVER	Black, special synthetic rubber cover - abrasion - heat and weather resistant; Smooth wrapped finish.
TEMPERATURE	-35° C to +70° C

CODE	Inner Diameter ID		Outside Diameter OD		Working Pressure		Burst Pressure		Theoretical Weight
	mm	inch	mm	inch	bar	psi	bar	psi	
CMH-20	51	1 1/4"	44	1 47/64"	20	290	60	870	1.100
CMN-24	38	1 1/2"	51	2"	20	290	60	870	1.270
CMH-32	51	2"	67	2 5/8"	20	290	50	725	2.250
CMH-2 1/2"	63	2 1/2"	79	3 7/64"	20	290	60	870	2.590
CMH-3"	76	3"	92	3 5/8"	20	290	60	870	2.800
CMH-3 5/32"	80	3 5/32"	96	3 25/32"	20	290	60	870	3.270
CMH-3 35/64"	90	3 35/64"	106	4 3/16"	20	290	60	870	3.800
CMH-4"	102	4"	118	4 41/64"	20	290	60	870	4.600
CMH-6"	152	6"	182	7 11/64"	20	290	60	870	12.350
CMH-8"	203	8"	234	9 7/32"	20	290	60	870	

BILFLEX